

EMERGENCY EXIT SIGNS

ARROW N

MATERIALS:

White, grey or black polycarbonate body

Plexi glass

MOUNTING:

Surface (wall, ceiling)

POWER SUPPLY:

Self contained – 220 - 240VAC/50 - 60Hz

Central battery – 220 - 240VAC/50 - 60Hz; 176 - 275VDC

Central battery FZLV – 24VDC

LIGHT SOURCE:

1W, 2W LED

CHARGING:

BASIC: max. 24h

STANDARD: max. 24h

PREMIUM: max. 12h; energy-saving electronic charger

AUTONOMY AND BATTERIES:

BASIC: 1h or 3h, Ni-Cd 3,6V batteries

STANDARD: 1h or 3h, Ni-Cd 3,6V batteries

PREMIUM: 1h or 3h, LiFePO₄ 6,4V batteries

INSULATION CLASS:

II or III

IP RATING:

IP41

VIEWING DISTANCE:

25m

AMBIENT TEMPERATURE:

t_a: 0°C - +40°C

OPTIONS:

SE – non maintained

SA – maintained

AT – autotest

PT – manual test button

RU – Rubic UNA central monitoring

FZLV – central battery FZLV 24VDC

CB – central battery

ADDITIONAL INFORMATION:

LED indicator signalizes mains power supply and battery charge

Deep discharge protection

III class of insulation of FZLV version



DIMENSIONS (mm):

